

CABLE TRAY SYSTEM

Straight Tray Covers

Vantrunk straight tray covers are 3m in length and are available in widths of 50mm to 900mm as standard. Covers are common for both closed and ventilated applications.

Fitting Type: CC-SL3 or CV-SL3

Straight Cable Tray Ventilated (Raised) Cover

Straight Cable Tray Closed (Non-Ventilated) Cover

Straight Cable Tray Cover Overall Dimensions & Fixing Centres

Wc

Tray Width mm	Cover Width Wc mm	Gauge T mm	Weight kg
50	59	1.2	2.51
75	84		3.17
100	109		3.92
150	159		5.43
200	209		6.74
225	234		7.70
300	309		9.96

Weights shown are for standard hot dip galvanised finish only, for Stainless Steel & Silicon Rich Steel weight conversion factors please refer to the Cable Tray technical section.

Fitting Covers

Vantrunk cable tray fitting covers are available in widths of 50mm to 900mm as standard. Covers are common for both closed and ventilated applications.

Fitting Type: CC-Fitting Type or CV-Fitting Type

Order details for all fittings except risers are as follows:

Tray Type - Cover Type - Tray Fitting Type - Width - Radius - Finish & Material - Gauge.

Omit the radius detail if the standard radius fitting is required.

Order example:

HR-CV-FE30-300-150R-GA-1.2 Vantrunk Heavy Duty Return Flange Cable Tray Ventilated Cover, 30° Flat Elbow, 300mm Wide, 150mm Radius, c/w Cover Fixing Kits, Hot Dip Galvanised Mild Steel, 1.2mm material thickness.

Order example:

HR-CC-FE90-750-300R-SS-1.0 Vantrunk Heavy Duty Return Flange Cable Tray Closed Cover, 90° Flat Elbow, 750mm Wide, 300mm Radius, c/w Cover Fixing Kits, Stainless Steel (316 Grade), 1.0mm material thickness.

Covers for inside and outside riser fittings are supplied pre-formed to angles of 30°, 45°, 60° or 90° to match the angle of the riser.